



LNS/LNK – rinsing hose

Rinsing hose suitable for industrial use particularly in paper mills.

Flexible, rope spiral reinforced.

LNS - with a fixed rubber spray nozzle at one end and a cuff in the other end. LNK - separate rubber spray nozzle, structurally similar to LNS-hose.

Temperature range: -40°C...+80°C

Tube: black SBR

Reinforcement: textile and rope spiral

Cover: red NR/EPDM, corrugated finish

Reinforcement: 3,2

Technical parameters

Product	Ø i.d.	Ø o.d.	Working press.	Vacuum	Bending radius	Weight	Length
-	mm	mm	MPa	max. MPa	mm	kg/m	m
LNK (spray nozzle only)							
LNK10019	19 / 9	31	1,0	-	60	0,40	0,60
LNK10025	25 / 10	36	1,0	-	60	0,40	0,70
LNK10032	32 / 12	43	1,0	-	60	0,60	0,70
LNK10038	38 / 12	49	1,0	-	60	0,70	0,60
LNK10040	40 / 12	51	1,0	-	60	0,70	0,70
LNK10050	40 / 12	61	1,0	-	60	0,80	0,70
LNS (hose spray with a spray nozzle end)							
LNS100202	19	31	1,0	-	110	0,60	10
LNS100202	19	31	1,0	-	110	0,60	15
LNS100202	19	31	1,0	-	110	0,60	20
LNS100250	25	36	1,0	-	130	0,80	10
LNS100251	25	36	1,0	-	130	0,80	15
LNS100252	25	36	1,0	-	130	0,80	20
LNS100320	32	43	1,0	-	170	0,90	15
LNS100321	32	43	1,0	-	170	0,90	15
LNS100322	32	43	1,0	-	170	0,90	20
LNS100380	38	49	1,0	-	200	1,00	10
LNS100381	38	49	1,0	-	200	1,00	15
LNS100382	38	49	1,0	-	200	1,00	20
LNS100400	40	51	1,0	-	220	1,10	10
LNS100401	40	51	1,0	-	220	1,10	15
LNS100402	40	51	1,0	-	220	1,10	20
LNS100500	50	61	1,0	-	200	1,40	10
LNS100501	50	61	1,0	-	200	1,40	15
LNS100502	50	61	1,0	-	200	1,40	20

i.d. - inner diameter, o.d. - outer diameter

Representation

Romex is a representative of 