



LACTO-TEK 1420 SL Pressure hose

Developed specially for food industry and other process industries with high hygienic demands.

Temperature range: -30°C...+80°C (temporarily washing with steam +130°C)

Tube: white NBR, food quality

Reinforcement: textile and steel spiral

Cover: blue NBR/PVC, wear resistant

Reinforcement: 4

NOTICE! Before using in food industries hoses must be washed with 5 % soda solution. The hoses can also be washed temporarily with hot water or steam. Hoses can be connected with swaged couplings or clamps.

Technical parameters

Product	Ø i.d.	Ø o.d.	Working press.	Vacuum	Bending radius	Weight	Length
-	mm	mm	MPa	max. MPa	mm	kg/m	m
1420SL025	25	37	1,0	0,09	60	0,90	40
1420SL040	40	53	1,0	0,09	110	1,50	40
1420SL050	50	66	1,0	0,09	140	2,20	40
1420SL051	51	62	1,0	0,09	140	1,80	40
1420SL065	65	79	1,0	0,09	180	2,60	40
1420SL075	75	91	1,0	0,09	220	3,30	40
1420SL076	76	92	1,0	0,09	220	3,30	40

i.d. - inner diameter, o.d. - outer diameter

Representation

Romex is a representative of 